



Long-duration energy storage technologies and applications



Scott Litzelman Ph.D.

Advanced Research Projects Agency – Energy (ARPA-E)

Outline

- Context behind the ARPA-E DAYS program
- Technology-to-Market: application space and examples
- Technology solutions: program portfolio and some recent results



LDES value unlocked at high VRE deployment levels



Firming Output of Variable Renewables





Ensuring System Resiliency



Back to the DAYS call: LCOS, duty cycle

Charge/discharge prices are rough estimates; not market projections








DAYS cost targets

10-100 hours of discharge at 5 ¢/kWh-cycle






Focus has shifted more from LCOS to CapEx

TECHNOLOGY-TO-MARKET



Assessing system value, especially capacity

Factors comprising system value of 4-hour storage in the Northeast U.S. under different renewable and storage penetration levels



D.S. Mallapragada, N.A. Sepulveda, J.D. Jenkins, *Applied Energy* **275**, 115390 (2020)



Recent capacity substitution examples

Oakland to Swap Jet-Fuel-Burning Peaker Plant for Urban Battery

The deal with Vistra will be the largest standalone storage facility contracted for a community-choice aggregator in California.

JULIAN SPECTOR JUNE 26, 2019







Ву:



Andy Colthorpe Editor

California Community Choice groups seek up to 500MW of long-duration energy storage

8 hours duration, in service by 2026



Peaker plant in Oakland replaced with 20 MW / 80 MWh of lithium-ion storage



Understanding LDES value: stakeholder outreach

Financial Partners





















Market Researchers







Utilities













OEMs









Trade Groups









Energy Buyers









Public Partners














TECHNOLOGY SOLUTIONS



Desired technology cost structure



<u>Assumptions</u>

- \$0.05/kWh differential per cycle
- Certain duty cycle
- \$25/kW-yr capacity payment




The DAYS portfolio


Thermal energy storage




Thermophotovoltaic (TPV) storage




Geomechanical storage



Pumped heat energy storage (PHES)



Electrochemical storage





The DAYS technical portfolio

Thermal energy storage





Thermophotovoltaic (TPV) storage





Geomechanical storage



Pumped heat energy storage (PHES)







Electrochemical storage















ZnBr₂ battery: simple design, cheap materials






Metric	Before ARPA-E	Current	Target
Cell BOM	\$120/kWh	\$70/kWh	\$25/kWh
Energy Density	8 Wh/L	60 Wh/L	120 Wh/L
RTE	60%	68%	75%
Self Discharge	20% / day	10% / day	5% / day
Cell Size	50 mWh	20 Wh	200 Wh






Overview of the Technology: Thermochemical Storage

$$MgO + 2MnO + \frac{1}{2}O_2 \leftrightarrow MgMn_2O_4$$



Quidnet stores energy as high-pressure water underground



- 1 Charge. Water pumped down the well into high-pressure storage lens
- 2 Discharge. High-pressure water flows up the well to drive a turbine

Modular, long-duration storage

1-10 MW per well, 10+ hours

Structural cost position

<50% capex of battery & pumped hydro, <**\$10 per** marginal kWh

Broad geological footprint

100+ TWh across multiple US basins

Mature execution supply chain



Summary

- LDES is a tool in decarbonization; serves a different role than storage today
- LDES is valuable at the system level, but need to translate that to individual customers
- The ARPA-E DAYS program and others (see right) are developing LDES technologies to do this

















